
Division of Environmental Remediation

Record of Decision
312 Maple Street Site
Environmental Restoration Project
Village of Endicott, Broome County, New York
Site Number B00168

January 2011

DECLARATION STATEMENT - RECORD OF DECISION

312 Maple Street Environmental Restoration Project Village of Endicott, Broome County, New York Site No. B00168

Statement of Purpose and Basis

The Record of Decision (ROD) presents the selected remedy for the 312 Maple Street site, an environmental restoration site. The selected remedial program was chosen in accordance with the New York State Environmental Conservation Law, 6 NYCRR Part 375, and is not inconsistent with the National Oil and Hazardous Substances Pollution Contingency Plan of March 8, 1990 (40CFR300), as amended.

This decision is based on the Administrative Record of the New York State Department of Environmental Conservation (the Department) for the 312 Maple Street site and the public's input to the Proposed Remedial Action Plan (PRAP) presented by the Department. A listing of the documents included as a part of the Administrative Record is included in Appendix B of the ROD.

Description of Selected Remedy

Based on the results of the remedial investigation/alternative analysis (RI/AA) for the 312 Maple Street site and the criteria identified for evaluation of alternatives, the Department has selected Enhanced Anaerobic Bioremediation and Site Management as the remedy. The components of the remedy are as follows:

1. A remedial design program would be implemented to provide the details necessary for the construction, operation, maintenance, and monitoring of the remedial program.
2. Enhanced anaerobic bioremediation applied through a network of injection wells to target the primary contaminants of concern in groundwater.
3. Operation, maintenance and monitoring of existing sub-slab depressurization systems.
4. The operation of the components of the remedy would continue until the remedial objectives have been achieved, or until the Department determines that continued operation is technically impracticable or not feasible.
5. Imposition of an institutional control in the form of an environmental easement for the controlled property that:
 - (a) requires the remedial party or site owner to complete and submit to the Department a periodic certification of institutional and engineering controls in accordance with Part 375-1.8 (h)(3);
 - (b) allows the use and development of the controlled property for restricted residential, commercial, and/or industrial use (land use is subject to local zoning laws);

- (c) restricts the use of groundwater as a source of potable or process water, without necessary water quality treatment as determined by the Department, NYSDOH or County DOH;
- (d) prohibits agriculture or vegetable gardens on the controlled property;
- (e) requires compliance with the Department approved Site Management Plan.

6. Since the remedy results in contamination remaining at the site that does not allow for unrestricted use, a Site Management Plan is required, which includes the following:

(a) an Institutional and Engineering Control Plan that identifies all use restrictions and engineering controls for the site and details the steps and media-specific requirements necessary to assure the following institutional and/or engineering controls remain in place and effective:

Institutional Controls: The Environmental Easement discussed in Paragraph 5 above.

Engineering Controls: The sub-slab depressurization systems discussed in Paragraph 3 above.

This plan includes, but is not limited to:

- (i) Excavation Management Plan which details the provisions for management of future excavations in areas of remaining contamination;
 - (ii) descriptions of the provisions of the environmental easement including any land use, groundwater water use restrictions;
 - (iii) provisions for the management and inspection of the identified engineering controls;
 - (iv) maintaining site access controls and Department notification; and
 - (v) the steps necessary for the periodic reviews and certification of the institutional and/or engineering controls;
- (b) a Monitoring Plan to assess the performance and effectiveness of the remedy. The plan includes, but is not limited to:
- (i) monitoring of groundwater to assess the performance and effectiveness of the remedy;
 - (ii) a schedule of monitoring and frequency of submittals to the Department;
 - (iii) provision to evaluate the potential for vapor intrusion for any buildings newly constructed on the site, including provision for mitigation of any impacts identified; provision to evaluate the potential for soil vapor intrusion for existing buildings if building use changes significantly or if a vacant building become occupied.
- (c) an Operation and Maintenance Plan to assure continued operation, maintenance, monitoring, inspection, and reporting of for any mechanical or physical components of the remedy. The plan includes, but is not limited to:
- (i) compliance monitoring of treatment systems to assure proper O&M as well as providing the data for any necessary permit or permit equivalent reporting;
 - (ii) maintaining site access controls and Department notification; and
 - (iii) providing the Department access to the site and O&M records.

7. Green remediation and sustainability efforts are considered in the design and implementation of the remedy to the extent practicable, including:
- using renewable energy sources
 - reducing green house gas emissions
 - conserving natural resources


New York State Department of Health Acceptance

The New York State Department of Health (NYSDOH) concurs that the remedy selected for this site is protective of human health.

Declaration

The selected remedy is protective of human health and the environment, complies with State and Federal requirements that are legally applicable or relevant and appropriate to the remedial action to the extent practicable, and is cost effective. This remedy utilizes permanent solutions and alternative treatment or resource recovery technologies, to the maximum extent practicable, and satisfies the preference for remedies that reduce toxicity, mobility, or volume as a principal element.

January 21, 2011
Date


Dale A. Desnoyers
Dale A. Desnoyers, Director
Division of Environmental Remediation

RECORD OF DECISION
312 Maple Street
Environmental Restoration Project
Village of Endicott, Broome County, New York
Site No. B00168
January 2011

SECTION 1: SUMMARY AND PURPOSE OF THE PROPOSED PLAN

The New York State Department of Environmental Conservation (the Department), in consultation with the New York State Department of Health (NYSDOH), has selected this remedy for the above referenced site. The disposal of hazardous waste at the site has resulted in threats to public health and the environment that are addressed by this remedy presented in this Record of Decision (ROD). The disposal of hazardous wastes at this site, as more fully described in Sections 5 of this document, have contaminated various environmental media. The proposed remedy, discussed in detail in Section 8, is intended to attain the remedial action objectives identified for this site in Section 6 for the protection of public health and the environment. This ROD identifies the selected remedy, summarizes the other alternatives considered, and discusses the reasons for the selected remedy. The Department has selected a final remedy for the site only after careful consideration of all comments received during the public comment period.

The 1996 Clean Water/ Clean Air Bond Act provides funding to municipalities for the investigation and cleanup of brownfields. Brownfields are abandoned, idled, or under-used properties where redevelopment is complicated by real or perceived environmental contamination. They typically are former industrial or commercial properties where operations may have resulted in environmental contamination. Brownfields often pose not only environmental, but legal and financial burdens on communities. Under the Environmental Restoration Program, the state provides grants to municipalities to reimburse up to 90 percent of eligible costs for site investigation and remediation activities. Once remediated, the property can then be reused.

The Department has issued this ROD in accordance with the requirements of New York State Environmental Conservation Law and Title 6 of the Official Compilation of Codes, Rules and Regulations of the State of New York, 6 NYCRR Part 375.

SECTION 2: SITE DESCRIPTION AND HISTORY

2.1: Location and Description

312 Maple Street (the site) is located on the southwest corner of Maple Street and North Duane Street in the Village of Endicott, Broome County (Figure 1). The site is approximately 0.93 acres in size and is comprised of two tax parcels with Tax Map ID Numbers 156.12-4-11 and 156.12-4-12. Three interconnected buildings and paved parking areas cover most of the site. A small vegetated area is located on the southwestern side of the site in an area formerly occupied by a rail spur. Currently, two of the three site buildings are used for wood cabinet manufacturing and leased office space. The third building is used primarily for storage. Adjacent parcels are currently used for a combination of residential and commercial purposes. Railroad tracks have been located adjacent to the site on the south since the early 1900s. The Former Canada Dry Bottling Facility

inactive hazardous waste disposal site (Site No. 704050) is located approximately 275 feet to the east.

Overburden encountered at the site generally consists of fill material (e.g. sands and gravels intermixed with ash, coal, and slag components) ranging from about two to seven feet thick overlying assumed proglacial fluvial deposited granular sand and gravel soil with lesser amounts of silt. Investigations at the site were focused on overburden soils within 20 feet of the ground surface.

The average depth to groundwater measured in monitoring wells at the site is approximately 14 feet below ground surface (bgs). Seasonal fluctuations in observed groundwater levels have been as high as three feet. The groundwater flow direction at the site is generally to the northwest or west-northwest.

The site topography is generally flat and typical pavement grades have been constructed to shed precipitation away from the buildings and towards either North Duane Street or Maple Street where it drains into the nearest storm water catch basin. The nearest surface water bodies to the site are Nanticoke Creek and the Susquehanna River at approximately one-half mile to the north and south, respectively.

2.2: Operational/Disposal History

From 1922 to the 1960's, the site was used for shoe manufacturing; from 1965 to 1981, the site was used for electronics assembly; and from 1988 to 1993, the site was used for manufacturing circuit boards and computer recycling. Portions of the southern side of the site were historically occupied by several coal companies and used for coal storage. Trichloroethylene (TCE) was used in the electronics manufacturing process for cleaning parts. TCE apparently spilled outside the buildings in the southeast portion of the site and also may have been released through discharges to three drywells located beneath on-site buildings.

2.3: Remedial History

The site remedial program is being performed by Broome County through the Department's Environmental Restoration Program (ERP).

Investigation activities that were implemented by Broome County prior to conducting the Remedial Investigation and Alternatives Analysis (RI/AA) include the following:

- Environmental Site Assessments completed in 1996.
- Environmental Investigation completed in 1999.
- Supplemental Environmental Site Investigation completed in 1999.

SECTION 3: LAND USE

The Department may consider the current, intended, and reasonable anticipated future land use of the site and its surroundings when assessing the nature and extent of contamination. For this site alternatives that may restrict the use of the site to restricted residential criteria as described in Part

375-1.8 (g) are being evaluated in addition to unrestricted use SCGs because data from the RI indicates that this restricted use level is achievable and would provide Broome County with additional options regarding land use planning. A comparison of the appropriate SCGs for the identified land use against the unrestricted use SCGs for the site contaminants is included in the tables for the media being evaluated in Section 5.1.2.

SECTION 4: ENFORCEMENT STATUS

Potentially Responsible parties (PRPs) are those who may be legally liable for contamination at a site. This may include past or present owners and operators, waste generators, and haulers. Since no viable PRPs have been identified, there are currently no ongoing enforcement actions. However, legal action may be initiated at a future date by the State to recover state response costs should PRPs be identified. Broome County will assist the state in its efforts by providing all information to the state which identifies PRPs. The County will also not enter into any agreement regarding response costs without the approval of the Department.

SECTION 5: SITE CONTAMINATION

A remedial investigation has been conducted to determine the nature and extent of contamination and to evaluate the alternatives for addressing the significant threats to human health and the environment.

5.1: Summary of the Remedial Investigation

The purpose of the Remedial Investigation (RI) was to define the nature and extent of any contamination resulting from previous activities at the site. The RI was conducted between May 2006 and October 2009. The field activities and findings of the investigation are described in the RI Report.

The following general activities are conducted during an RI:

- Research of historical information,
- Soil borings and monitoring well installations,
- Sampling of surface and subsurface soils, groundwater and soil vapor,
- Ecological and Human Health Exposure Assessments.

5.1.1: Standards, Criteria and Guidance (SCGs)

The remedy must conform to the promulgated standards and criteria that are directly applicable, or that are relevant and appropriate. The selection of a remedy must also take into consideration guidance, as appropriate. Standards, criteria and guidance are hereafter called SCGs.

To determine whether the contaminants identified in various media are present at levels of concern, the data from the RI were compared to media-specific SCGs. The Department has developed SCGs for groundwater, surface water, sediments, and surface and subsurface soil. The NYSDOH has developed SCGs for drinking water and soil vapor intrusion. The tables found in the following Sections list the applicable SCG in the footnotes. For a full listing of all SCGs see: <http://www.dec.ny.gov/regulations/61794.html>.

Based on the RI results, in comparison to the SCGs and potential public health and environmental exposure routes, certain media and areas of the site require remediation. These are summarized in Section 5.1.2. More complete information can be found in the RI Report.

5.1.2: Nature and Extent of Contamination

This section describes the findings of the Remedial Investigation. As described in the RI Report, waste/source materials were identified at the site and are impacting groundwater, soil, and/or soil vapor.

Groundwater

Groundwater samples were collected from overburden monitoring wells. The samples were collected to assess groundwater conditions on- and off-site. The results indicate that contamination in the shallow groundwater at the site exceeds the SCGs for volatile organic compounds (VOCs) and heavy metal compounds (metals). Table 1 includes all contaminants that exceed the groundwater and drinking water SCGs.

| Table 1 - Groundwater | | | |
|------------------------------|---|------------------------------|--------------------------------|
| Detected Constituents | Concentration Range Detected (ppb)^a | SCG^b (ppb) | Frequency Exceeding SCG |
| VOCs | | | |
| Trichloroethene | 2.3 – 1,600 | 5 | 12 of 15 |
| Metals | | | |
| Hexavalent Chromium | 48 - 1,200 | 50 | 3 of 5 |
| Iron | 44.5 - 590 | 300 | 1 of 5 |
| Sodium | 33,600 – 434,000 | 20,000 | 2 of 5 |
| Thallium | 1.7 – 2.0 | 0.5 | 2 of 5 |

a - ppb: parts per billion, which is equivalent to micrograms per liter, ug/L, in water.

b - SCG: Standards, Criteria and Guidance - Ambient Water Quality Standards and Guidance Values (TOGs 1.1.1), 6 NYCRR Part 703, Surface Water and Groundwater Quality Standards and Part 5 of the New York State Sanitary Code (10 NYCRR Part 5).

The primary groundwater contaminants of concern at the site are trichloroethene (TCE) associated with the previous use of the site for electronics manufacturing and hexavalent chromium associated with the previous use of the site for shoe manufacturing (i.e., leather tanning). The concentrations and

distribution of the contaminants of concern are shown on Figure 2. The other metals listed in Table 1 are more isolated in extent. However, they are likely associated with previous site uses.

Groundwater contamination migrating off-site to the north and northwest combines with contamination associated with former Canada Dry Plant inactive hazardous waste disposal site. Contamination that exists beyond the limits shown on Figure 2 has been defined as part of the remedial investigation for the Former Canada Dry Bottling Facility site. The location of the Former Canada Dry site and the remedial investigation study area are shown on Figure 3.

Based on the findings of the RI, the disposal of hazardous waste has resulted in the contamination of groundwater. The site contaminants that are considered to be the primary contaminants of concern which will drive the remediation of groundwater to be addressed by the remedy selection process are TCE and hexavalent chromium.

Soil

Surface and subsurface soil samples were collected at the site during the RI. Soil samples were collected both on- and off-site to assess direct human exposure and soil contamination impacts to groundwater. Soil samples were collected from ground surface to a depth of 16 feet. The results indicate that soils exceed the unrestricted use SCGs for VOCs and metals. Table 2 includes all contaminants that exceed the unrestricted use SCGs.

| Detected Constituents | Concentration Range Detected (ppm) ^a | Unrestricted SCG ^b (ppm) | Frequency Exceeding Unrestricted SCG | Restricted Residential SCG ^c (ppm) | Frequency Exceeding Restricted SCG |
|-----------------------|---|-------------------------------------|--------------------------------------|---|------------------------------------|
| VOCs | | | | | |
| Trichloroethene | 0.0034 – 110 | 0.47 | 12 of 40 | 21 | 6 of 40 |
| Metals | | | | | |
| Cadmium | 0.82 – 7.7 | 2.5 | 1 of 8 | 4.3 | 1 of 8 |
| Copper | 9.9 – 321 | 50 | 2 of 8 | 270 | 1 of 8 |

a - ppm: parts per million, which is equivalent to milligrams per kilogram, mg/kg, in soil.

b - SCG: Part 375-6.8(a), Unrestricted Use Soil Cleanup Objectives.

c - SCG: Part 375-6.8(b), Restricted Residential Soil Cleanup Objectives.

The trichloroethene (TCE) contamination in soil is associated with the former on-site electronics manufacturing and is typically present in the soil from near ground surface to a depth of approximately four feet. Remaining soil contamination appears isolated to an off-site area immediately adjacent to the where the on-site soil excavation Interim Remedial Measure (IRM) was performed. The IRM is described in Section 5.2. The concentrations and distribution of TCE soil contamination are shown on Figure 4.

The metals contamination in soil was isolated to an area beneath one of the drywells on-site and was addressed during the IRMs described in Section 5.2.

Based on the findings of the Remedial Investigation, the disposal of hazardous waste has resulted in the contamination of soil. The site contaminant identified in soil which is considered to be the primary contaminant of concern to be addressed by the remedy selection process is TCE.

Soil Vapor Intrusion

The evaluation of the potential for soil vapor intrusion resulting from the presence of site related soil or groundwater contamination was evaluated by the sampling of sub-slab soil vapor under structures, and indoor air inside structures. At this site, due to the presence of buildings in the impacted area a full suite of samples were collected to evaluate whether soil vapor intrusion was occurring.

Soil vapor intrusion samples (a combined sample set including sub-slab, indoor, and outside air) were collected from 21 residential, commercial and/or industrial buildings including those on-site. Sampling was performed in 2006, 2007 and 2008. Figure 5 shows the general locations of the buildings sampled. Based on the air sampling results, sub-slab depressurization (SSD) systems were installed at the three on-site buildings and at three off-site commercial buildings. Overall, the results of the air sampling effort indicated that no sampling of additional buildings was needed to assist with the completion of the RI.

The primary soil vapor contaminant is trichloroethene (TCE), which is associated with former on-site electronics manufacturing.

Based on the findings of the Remedial Investigation, the disposal of hazardous waste has resulted in the contamination of soil vapor. The site contaminant that is considered to be the primary contaminant of concern which will drive the remediation of soil vapor to be addressed by the remedy selection process is TCE.

5.2: Interim Remedial Measures

An interim remedial measure (IRM) is conducted at a site when a source of contamination or exposure pathway can be effectively addressed before issuance of the Record of Decision.

Based on previously completed site investigations, it was determined that approximately 250 cubic yards of TCE- contaminated soil was present in the southeast portion of site. An IRM was conducted in 2006 which included excavation and off-site disposal of the TCE-contaminated soil. The approximate limits of the IRM excavation are shown on Figure 4. Additionally in 2006, sediment/soil at the bottom and beneath two drywells was removed and disposed off-site. The drywells were backfilled with concrete up to the existing floor grade.

Mitigation measures (i.e., installation of SSD systems) were also taken at the on-site buildings and three off-site buildings to address current and/or potential indoor air contamination of volatile organic compounds associated with soil vapor intrusion.

Excavation of TCE contaminated soil identified off-site on the Norfolk Southern Rail Road property will also be conducted as an IRM. All off-site soils located in the vadose zone (above the water table) which exceed unrestricted SCGs will be excavated and transported off-site for disposal. The approximate location and areal extent of excavation is shown on Figure 4. It is estimated that 50 cubic yards of soil will be removed. Clean fill will then be brought in to replace the excavated soil and establish the designed grades at the site.

5.3: Summary of Human Exposure Pathways:

This section describes the current or potential human exposures (the way people may come in contact with contamination) that may result from the site contamination. A more detailed discussion of the human exposure pathways can be found in the RI report available at the document repository. An exposure pathway describes the means by which an individual may be exposed to contaminants originating from a site. An exposure pathway has five elements: [1] a contaminant source, [2] contaminant release and transport mechanisms, [3] a point of exposure, [4] a route of exposure, and [5] a receptor population.

Contaminant release and transport mechanisms carry contaminants from the source to a point where people may be exposed. The exposure point is a location where actual or potential human contact with a contaminated medium may occur. The route of exposure is the manner in which a contaminant actually enters or contacts the body (e.g., ingestion, inhalation, or direct contact). The receptor population is the people who are, or may be, exposed to contaminants at a point of exposure.

An exposure pathway is complete when all five elements of an exposure pathway exist. An exposure pathway is considered a potential pathway when one or more of the elements currently does not exist, but could in the future.

Currently, there are no complete exposure pathways associated with the site. Exposure to site-related contaminants via soil vapor intrusion was previously identified as a completed exposure pathway for the on-site buildings and some buildings adjacent to the site. As a result, sub-slab depressurization systems were installed and continue to operate to ensure that site-related contaminants do not affect the indoor air of buildings on or near the site.

There is a potential for people to come into contact with contaminated surface or subsurface soil if they trespass or conduct ground-intrusive activities in the southeast area of the site or on the adjacent railroad property. People are not expected to come in contact with contaminated soil on the remainder of the site because buildings and pavement cover most of the site. People are not currently being exposed to the contaminated groundwater because groundwater in the vicinity of the site is not used as a source of drinking water and the contamination does not extend to the public water supply wells.

5.4: Summary of Environmental Assessment

This section summarizes the assessment of existing and potential future environmental impacts presented by the site. Environmental impacts may include existing and potential future exposure pathways to fish and wildlife receptors, wetlands, groundwater resources, and surface water.

The 312 Maple Street site is located in an urban area, with nearly the entire site covered by a building and paved parking lots. Significant portions of the land surrounding the site are also covered by the railroad, pavement and/or buildings. Based on the location of the site and the conditions summarized above and in Section 2.1, a Fish and Wildlife Impact Analysis was not included in the RI.

Surface water resources near the site include Nanticoke Creek and the Susquehanna River at approximately one-half mile to the north and south, respectively. No current or potential site-related surface water impacts have been identified.

Groundwater resources at the site include an overburden groundwater unit. The generalized hydrogeologic characteristics of the overburden groundwater unit are presented in Section 2.1. Site-related contamination is impacting a sole source, principal/primary aquifer that is used as a source of potable water. The remedy must address the impacts of the site to the groundwater aquifer.

SECTION 6: SUMMARY OF THE REMEDIATION OBJECTIVES

The objectives for the remedial program have been established through the remedy selection process stated in 6 NYCRR Part 375. The goal for the remedial program is to restore the site to pre-disposal conditions to the extent feasible. At a minimum, the remedy shall eliminate or mitigate all significant threats to public health and the environment presented by the contamination identified at the site through the proper application of scientific and engineering principles.

The remedial objectives for this site are:

Public Health Protection

Groundwater

- Prevent people from drinking groundwater with contaminant levels exceeding drinking water standards.
- Prevent contact with contaminated groundwater.
- Prevent inhalation of contaminants from groundwater.

Soil

- Prevent ingestion/direct contact with contaminated soil.
- Prevent inhalation of contaminants volatilizing from the soil.

Soil Vapor

- Mitigate impacts to public health resulting from existing, or the potential for, soil vapor intrusion into the indoor air of buildings at or near a site.

Environmental Protection

Groundwater

- Restore the groundwater aquifer to meet ambient groundwater quality criteria, to the extent feasible.

Soil

- Prevent migration of contaminants that would result in groundwater or surface water contamination.

SECTION 7: SUMMARY OF THE EVALUATION OF ALTERNATIVES

To be selected the remedy must be protective of human health and the environment, be cost-effective, comply with other statutory requirements, and utilize permanent solutions, alternative technologies or resource recovery technologies to the maximum extent practicable. Potential remedial alternatives for the Site were identified, screened and evaluated in the alternative analysis report which is available at the document repositories established for this site.

A summary of the remedial alternatives that were considered for this site is presented below. Cost information is presented in the form of present worth, which represents the amount of money invested in the current year that would be sufficient to cover all present and future costs associated with the alternative. This enables the costs of remedial alternatives to be compared on a common basis. As a convention, a time frame of 30 years is used to evaluate present worth costs for alternatives with an indefinite duration. This does not imply that operation, maintenance, or monitoring would cease after 30 years if remediation goals are not achieved.

7.1: Description of Remedial Alternatives

The following alternatives were considered to address the contaminated media identified at the site as described in Section 5:

Alternative 1: No Further Action

The No Further Action Alternative recognizes the remediation of the site completed by the IRM(s) described in Section 5.2. This alternative leaves the site in its present condition and does not provide any additional protection of the environment.

Alternative 2: Monitored Natural Attenuation and Site Management

This alternative would include groundwater monitoring to assess the natural degradation of contaminants; operation, maintenance and monitoring of the existing SSD systems; and imposition of an environmental easement to restrict land use to restricted-residential use, prohibit groundwater use, and certify continued operation and maintenance of the SSD systems.

The groundwater monitoring would include periodic sampling of the existing monitoring wells (i.e., MW-1 through MW-8) plus one upgradient (i.e., background) monitoring well for analysis of VOCs and indicator parameters.

| | |
|--|-----------------|
| <i>Present Worth:</i> | <i>\$94,100</i> |
| <i>Capital Cost:</i> | <i>\$13,000</i> |
| <i>Annual Costs (years 1 and 2):</i> | <i>\$21,800</i> |
| <i>Annual Costs (years 3-30):</i> | <i>\$13,900</i> |

Alternative 3: Enhanced Anaerobic Bioremediation and Site Management

Enhanced anaerobic bioremediation involves the addition of an electron donor to the subsurface for use by local microorganisms capable of degrading volatile organic compounds found in soil and/or groundwater. The electron donor is introduced into the subsurface via injection points. The microorganisms (i.e., dechlorinating bacteria) use the electron donor, ultimately replacing chlorine atoms with hydrogen atoms in a process known as reductive dechlorination. Reductive dechlorination results in the step-by-step biological degradation of chlorinated contaminants such as trichloroethene (TCE) and its breakdown products. Several reductive dechlorination reagents are commercially available. At this site, the electron donors would be applied through a network of injection points to target the primary contaminant of concern, TCE.

Prior to the full implementation of this technology, pre-design investigations and on-site pilot testing would be conducted to more clearly define design parameters. For full-scale implementation of this technology, it is estimated that approximately 18 injection points would be installed. It is estimated that the electron donors would be applied in one injection event. Monitoring would be conducted to assess the effectiveness of remediation. Figure 6 shows the conceptual layout for this alternative.

This alternative would also include operation, maintenance and monitoring of the existing SSD systems; and imposition of an environmental easement to restrict land use to restricted-residential use, prohibit groundwater use, and certify continued operation and maintenance of the SSD systems.

| | |
|---|------------------|
| <i>Present Worth:</i> | <i>\$141,000</i> |
| <i>Capital Cost:</i> | <i>\$56,700</i> |
| <i>Annual Costs (years 1 through 4):</i> | <i>\$13,900</i> |
| <i>Annual Costs (years 5 through 30):</i> | <i>\$3,000</i> |

7.2 Evaluation of Remedial Alternatives

The criteria to which potential remedial alternatives are compared are defined in 6 NYCRR Part 375, which sets forth the requirements for the remediation of inactive hazardous waste disposal sites in New York. A detailed discussion of the evaluation criteria and comparative analysis is included in the alternative analysis report.

The first two evaluation criteria are termed “threshold criteria” and must be satisfied in order for an alternative to be considered for selection.

1. Protection of Human Health and the Environment. This criterion is an overall evaluation of each alternative’s ability to protect public health and the environment.

2. Compliance with New York State Standards, Criteria, and Guidance (SCGs). Compliance with SCGs addresses whether a remedy will meet environmental laws, regulations, and other standards and criteria. In addition, this criterion includes the consideration of guidance which the Department has determined to be applicable on a case-specific basis.

The next six “primary balancing criteria” are used to compare the positive and negative aspects of each of the remedial strategies.

3. Long-term Effectiveness and Permanence. This criterion evaluates the long-term effectiveness of the remedial alternatives after implementation. If wastes or treated residuals remain on-site after the selected remedy has been implemented, the following items are evaluated: 1) the magnitude of the remaining risks, 2) the adequacy of the engineering and/or institutional controls intended to limit the risk, and 3) the reliability of these controls.

4. Reduction of Toxicity, Mobility or Volume. Preference is given to alternatives that permanently and significantly reduce the toxicity, mobility or volume of the wastes at the site.

5. Short-term Impacts and Effectiveness. The potential short-term adverse impacts of the remedial action upon the community, the workers, and the environment during the construction and/or implementation are evaluated. The length of time needed to achieve the remedial objectives is also estimated and compared against the other alternatives.

6. Implementability. The technical and administrative feasibility of implementing each alternative are evaluated. Technical feasibility includes the difficulties associated with the construction of the remedy and the ability to monitor its effectiveness. For administrative feasibility, the availability of the necessary personnel and materials is evaluated along with potential difficulties in obtaining specific operating approvals, access for construction, institutional controls, and so forth.

7. Cost-Effectiveness. Capital costs and annual operation, maintenance, and monitoring costs are estimated for each alternative and compared on a present worth basis. Although cost-effectiveness is the last balancing criterion evaluated, where two or more alternatives have met the requirements of the other criteria, it can be used as the basis for the final decision. The costs for each alternative are presented in the Remedial Alternatives Cost Table.

**Table 3
Remedial Alternative Costs**

| Remedial Alternative | Capital Cost (\$) | Annual Costs (\$) | Total Present Worth (\$) |
|---|--------------------------|---|---------------------------------|
| No Further Action | 0 | 0 | 0 |
| Monitored Natural Attenuation and Site Management | 13,000 | 21,800 (years 1-2) 13,900 (years 3-30) | 94,100 |
| Enhanced Anaerobic Bioremediation and Site Management | 56,700 | 13,900 (years 1-4) 3,000 (years 5-30) | 141,000 |

8. Land Use. When cleanup to pre-disposal conditions is determined to be infeasible, the Department may consider the current, intended, and reasonable anticipated future land use of the site and its surroundings in the selection of the soil remedy.

The final criterion, Community Acceptance, is considered a “modifying criterion” and is taken into account after evaluating those above. It is evaluated after public comments on the Proposed Remedial Action Plan have been received.

9. Community Acceptance. Concerns of the community regarding the investigation, the evaluation of alternatives, and the PRAP have been evaluated. The responsiveness summary (Appendix A) presents public comments received and the manner in which the Department addressed the concerns raised. No public comments were received.

SECTION 8: SUMMARY OF THE SELECTED REMEDY

Based on the Administrative Record (Appendix B) and the discussion presented below, the Department has selected Alternative 3 (Enhanced Anaerobic Bioremediation and Site Management) as the remedy for this site. The elements of this remedy are described at the end of this section.

8.1 Basis for Selection

The selected remedy is based on the results of the RI and the evaluation of alternatives.

Alternative 3 is selected because, as described below, it satisfies the threshold criteria and provides the best balance of the balancing criterion described in Section 7.2. It would achieve the remediation goals for the site by providing the greatest permanent reduction in the toxicity, mobility, or volume of contamination in groundwater and creating the conditions necessary to restore groundwater quality to pre-release conditions to the extent practicable. The reduction of contaminants in groundwater at the site is expected to have a correlative impact on soil vapor contamination.

Alternative 1 (No Further Action) with no institutional controls and no site management does not provide sufficient protection to public health and the environment. Groundwater sampling has not shown TCE breakdown products that are typically present when natural attenuation of TCE is occurring. Therefore, Alternative 2 may not provide overall protection to public health and the environment. Failing to meet the threshold criteria, Alternatives 1 and 2 will not be evaluated further.

Alternative 3 is protective of public health and the environment, complies with the SCGs, and addresses the remedial goals and objectives for the site. Alternative 3 is expected to achieve the remedial goals and objectives in 5 years or less.

The estimated present worth cost to implement the remedy is \$141,000. The cost to construct the remedy is estimated to be \$56,700 and the estimated average annual costs range from \$13,900 for years 1 through 4 to \$3,000 for years 5 through 30.

8.2 Elements of the Selected Remedy

The elements of the selected restricted use remedy are as follows:

1. A remedial design program would be implemented to provide the details necessary for the construction, operation, maintenance, and monitoring of the remedial program.
2. Enhanced anaerobic bioremediation applied through a network of injection wells to target the primary contaminants of concern in groundwater.
3. Operation, maintenance and monitoring of existing sub-slab depressurization systems.

4. The operation of the components of the remedy would continue until the remedial objectives have been achieved, or until the Department determines that continued operation is technically impracticable or not feasible.
5. Imposition of an institutional control in the form of an environmental easement for the controlled property that:
 - (a) requires the remedial party or site owner to complete and submit to the Department a periodic certification of institutional and engineering controls in accordance with Part 375-1.8 (h)(3);
 - (b) allows the use and development of the controlled property for restricted residential, commercial, and/or industrial use (land use is subject to local zoning laws);
 - (c) restricts the use of groundwater as a source of potable or process water, without necessary water quality treatment as determined by the Department, NYSDOH or County DOH;
 - (d) prohibits agriculture or vegetable gardens on the controlled property;
 - (e) requires compliance with the Department approved Site Management Plan.
6. Since the remedy results in contamination remaining at the site that does not allow for unrestricted use, a Site Management Plan is required, which includes the following:
 - (a) an Institutional and Engineering Control Plan that identifies all use restrictions and engineering controls for the site and details the steps and media-specific requirements necessary to assure the following institutional and/or engineering controls remain in place and effective:

Institutional Controls: The Environmental Easement discussed in Paragraph 5 above.

Engineering Controls: The sub-slab depressurization systems discussed in Paragraph 3 above.

This plan includes, but is not limited to:


- (i) Excavation Management Plan which details the provisions for management of future excavations in areas of remaining contamination;
 - (ii) descriptions of the provisions of the environmental easement including any land use, groundwater water use restrictions;
 - (iii) provisions for the management and inspection of the identified engineering controls;
 - (iv) maintaining site access controls and Department notification; and
 - (v) the steps necessary for the periodic reviews and certification of the institutional and/or engineering controls;
- (b) a Monitoring Plan to assess the performance and effectiveness of the remedy. The plan includes, but is not limited to:
- (i) monitoring of groundwater to assess the performance and effectiveness of the remedy;
 - (ii) a schedule of monitoring and frequency of submittals to the Department;

- (iii) provision to evaluate the potential for vapor intrusion for any buildings newly constructed on the site, including provision for mitigation of any impacts identified;
 - (iv) provision to evaluate the potential for soil vapor intrusion for existing buildings if building use changes significantly or if a vacant building become occupied.
- (c) an Operation and Maintenance Plan to assure continued operation, maintenance, monitoring, inspection, and reporting of for any mechanical or physical components of the remedy. The plan includes, but is not limited to:
- (i) compliance monitoring of treatment systems to assure proper O&M as well as providing the data for any necessary permit or permit equivalent reporting;
 - (ii) maintaining site access controls and Department notification; and
 - (iii) providing the Department access to the site and O&M records.
7. Green remediation and sustainability efforts are considered in the design and implementation of the remedy to the extent practicable, including:
- using renewable energy sources
 - reducing green house gas emissions
 - conserving natural resources

SECTION 9: HIGHLIGHTS OF COMMUNITY PARTICIPATION



As part of the remedial investigation process, a number of Citizen Participation activities were undertaken to inform and educate the public about conditions at the site and the potential remedial alternatives. The following public participation activities were conducted for the site:

- Repositories for documents pertaining to the site were established
- A public contact list, which included nearby property owners, elected officials, local media and other interested parties, was established.
- A public meeting was held on November 30, 2010 to present and receive comment on the PRAP.



DRAWN BY: DEW
 DATE: OCTOBER 2009

GZA GeoEnvironmental of New York

BROOME COUNTY DEPARTMENT OF PLANNING AND ECONOMIC DEVELOPMENT
 312 MAPLE STREET
 VILLAGE OF ENDICOTT, NEW YORK

ERP SITE No. B-00168-7


LOCUS PLAN

PROJECT No.
21.0056127.00

FIGURE No.
1

NOTE:
 BASE MAP ADAPTED FROM U.S.G.S. TOPOGRAPHIC MAPS DOWNLOADED FROM TERRASERVER.MICROSOFT.COM





LEGEND:

- + **MW-5**
 (820 ppb)
 (180 ppb)
 (1200 ppb)
 (890 ppb)

APPROXIMATE LOCATION AND DESIGNATION OF MONITORING WELL. TCE CONCENTRATION IN PPB FROM SAMPLES COLLECTED FOR ANALYSIS IN PARENTHESIS.
 2008 TCE VALUES IN **BLUE**
 2006 TCE VALUES IN **RED**
 SEPTEMBER 2008 Cr⁺⁶ VALUES IN **GREEN**
 APRIL 2008 Cr⁺⁶ VALUES IN **ORANGE**
 NT = NOT TESTED AS MONITORING WELL WAS NOT PRESENT AT THE SAMPLE TIME
 ND = NOT DETECTED



TCE CONTOUR LINE REPRESENTS CONCENTRATIONS IN ppb AND IS BASED ON 2008 SAMPLE RESULTS


NOTES:

1. BASE MAP ADAPTED FROM A 2002 AERIAL PHOTOGRAPH DOWNLOADED FROM http://www.nysgis.state.ny.us/gateway/mg/interactive_main.html AND FIELD OBSERVATIONS.
2. THE SIZE AND LOCATION OF EXISTING SITE FEATURES SHOULD BE CONSIDERED APPROXIMATE.



DRAWN BY: DEW
 DATE: OCTOBER 2009

GZA GeoEnvironmental of New York





BROOME COUNTY DEPARTMENT OF PLANNING AND ECONOMIC DEVELOPMENT
 312 MAPLE STREET
 VILLAGE OF ENDICOTT, NEW YORK
ERP SITE No. B-00168-7

MONITORING WELL LOCATIONS AND TCE CONCENTRATION CONTOURS FROM 2006 AND 2008 GROUNDWATER SAMPLES

PROJECT No.
21.0056127.00

FIGURE No.
2




312 Maple St.

Canada Dry Bottling Facility



Former Canada Dry Bottling Facility Study Area

-  Groundwater Contours July 2008
-  Generalized Groundwater Flow Direction
-  Canada Dry Study Area Bounds
-  Sites w/ Known Volatile Organic Compounds




| | | |
|---|--|-----------------|
| DRAWN BY: NYSDEC  | DATE: September, 2010 <small>Created in ArcGIS 9.3 UNAUTHORIZED DUPLICATION IS A VIOLATION OF APPLICABLE LAWS</small> | FIGURE 3 |
| New York State Department of Environmental Conservation Division of Environmental Remediation | | |


GZA-T:\PROJECTS\106106\106127 Broome Co SI-RAR\ERP Figures\FIGURE 4.dwg [Figure 4] September 08, 2010 - 11:52am daniel.wulf

© 2009 GZA GeoEnvironmental of New York




LEGEND:


-  **SP-11 (13)** APPROXIMATE LOCATION OF SOIL PROBE AND TCE CONCENTRATION IN ppm FROM SAMPLES COLLECTED FOR ANALYSIS (NT = NOT TESTED)
-  **MW-1** APPROXIMATE LOCATION AND DESIGNATION OF EXISTING MONITORING WELL
-  **DRY WELL #1** APPROXIMATE LOCATION AND DESIGNATION OF DRYWELL CLOSURE




NOTES:

1. BASE MAP ADAPTED FROM A 2002 AERIAL PHOTOGRAPH DOWNLOADED FROM http://www.nysgis.state.ny.us/gateway/mg/interactive_main.html, A SURVEY PLAN PROVIDED BY THE CLIENT, AND FIELD OBSERVATIONS.
2. THE SIZE AND LOCATION OF EXISTING SITE FEATURES SHOULD BE CONSIDERED APPROXIMATE.



| | |
|---|---|
| <p>DRAWN BY: DEW DATE: OCTOBER 2009</p> |  <p>GZA GeoEnvironmental of New York</p> |
| <p>APPROXIMATE SCALE IN FEET AS SHOWN</p> | <p>BROOME COUNTY DEPARTMENT OF PLANNING AND ECONOMIC DEVELOPMENT 312 MAPLE STREET VILLAGE OF ENDICOTT, NEW YORK ERP SITE No. B-00168-7 RAILROAD PROPERTY SOIL DELINEATION AND IRM LOCATIONS</p> |
| <p>PROJECT No. 21.0056127.00</p> | |
| <p>FIGURE No. 4</p> | |



LAND USE LEGEND:

- COMMERCIAL
- COMMUNITY SERVICES
- INDUSTRIAL
- MULTI-RESIDENTIAL
- RECREATIONAL
- RESIDENTIAL
- VACANT

EVENTS 1 AND 2 SAMPLING LEGEND (2006):

- STRUCTURE 5 (COMMERCIAL)
- STRUCTURE 2 (COMMERCIAL)
- STRUCTURE 3 (RESIDENCE)
- STRUCTURE 6 (COMMERCIAL)
- STRUCTURE 7 (MULTI-FAMILY RESIDENCE)
- STRUCTURE 1 (MULTI-FAMILY RESIDENCE)
- STRUCTURE 4 (COMMERCIAL)
- STRUCTURE 10 (MULTI-FAMILY RESIDENCE)
- STRUCTURE 11 (SINGLE-FAMILY RESIDENCE)
- STRUCTURE 12 (MULTI-FAMILY RESIDENCE)
- STRUCTURE 9 (COMMERCIAL)
- STRUCTURE 8 (COMMERCIAL)
- STRUCTURE 13 (SINGLE-FAMILY RESIDENCE)

EVENT 3 SAMPLING LEGEND (2007-2008):

- RESAMPLED STRUCTURES :**
- STRUCTURE 9 (COMMERCIAL)
 - STRUCTURE 5 (COMMERCIAL)
 - STRUCTURE 13 (SINGLE FAMILY RESIDENCE)
 - STRUCTURE 1 (MULTI-FAMILY RESIDENCE)
 - STRUCTURE 8 (COMMERCIAL)
- STRUCTURES SAMPLED 1st TIME:**
- STRUCTURE 21 (SINGLE FAMILY RESIDENCE) (SEE NOTE 3)
 - STRUCTURE 17 (MIXED COMMERCIAL/RESIDENTIAL)
 - STRUCTURE 14 (MULTI-FAMILY RESIDENCE)
 - STRUCTURE 15 (SINGLE FAMILY RESIDENCE)
 - STRUCTURE 16 (COMMERCIAL)
 - STRUCTURE 20 (MULTI-FAMILY RESIDENCE)
 - STRUCTURE 19 (MULTI-FAMILY RESIDENCE)
 - STRUCTURE 18 (MULTI-FAMILY RESIDENCE)


LEGEND:

- A1 APPROXIMATE LOCATION AND DESIGNATION OF AMBIENT/OUTDOOR AIR SAMPLE (EVENTS 1-2, 2006)
- A8 APPROXIMATE LOCATION AND DESIGNATION OF AMBIENT/OUTDOOR AIR SAMPLE (EVENT 3, 2007-08)

NOTES:

1. BASE MAP ADAPTED FROM A LAND USE MAP DOWNLOADED FROM <http://broomegis.co.broome.ny.us/website/gisweb/portal.htm> AND FIELD OBSERVATIONS.
2. THE SIZE AND LOCATION OF EXISTING SITE FEATURES SHOULD BE CONSIDERED APPROXIMATE.
3. GZA ATTEMPTED TO COLLECT SAMPLES FROM THE STRUCTURE 21, HOWEVER THE OCCUPANT/OWNER DECLINED ACCESS/SAMPLING ON SEVERAL OCCASIONS. GZA CONTACTED THE OCCUPANT/OWNER BOTH IN PERSON AND VIA MAIL REQUEST.

| | | |
|-------------------------------|--------------------|---|
| DRAWN BY: DEW | DATE: OCTOBER 2009 | |
| APPROXIMATE SCALE IN FEET | | BROOME COUNTY DEPARTMENT OF PLANNING AND ECONOMIC DEVELOPMENT 312 MAPLE STREET VILLAGE OF ENDICOTT, NEW YORK ERP SITE No. B-00168-7 ON-SITE AND OFF-SITE SOIL VAPOR SAMPLING PLAN |
| PROJECT No. | | 21.0056127.00 |
| FIGURE No. | | 5 |



LEGEND:

MW-5
 (820 ppb)
 (180 ppb)
 (1200 ppb)
 (890 ppb)

APPROXIMATE LOCATION AND DESIGNATION OF MONITORING WELL. TCE CONCENTRATION IN PPB FROM SAMPLES COLLECTED FOR ANALYSIS IN PARENTHESIS.
 2008 TCE VALUES IN **BLUE**
 2006 TCE VALUES IN **RED**
 SEPTEMBER 2008 Cr⁶ VALUES IN **GREEN**
 APRIL 2008 Cr⁶ VALUES IN **ORANGE**
 NT = NOT TESTED AS MONITORING WELL WAS NOT PRESENT AT THE SAMPLE TIME
 ND = NOT DETECTED



APPROXIMATE LOCATION OF PROPOSED INJECTION POINTS



TCE CONTOUR LINE REPRESENTS CONCENTRATIONS IN ppb AND IS BASED ON 2008 SAMPLE RESULTS

NOTES:

1. BASE MAP ADAPTED FROM A 2002 AERIAL PHOTOGRAPH DOWNLOADED FROM http://www.nysgis.state.ny.us/gateway/mg/interactive_main.html AND FIELD OBSERVATIONS.
2. THE SIZE AND LOCATION OF EXISTING SITE FEATURES SHOULD BE CONSIDERED APPROXIMATE.



DRAWN BY: MDK

DATE: OCTOBER 2009

GZA GeoEnvironmental of New York



APPROXIMATE SCALE IN FEET



BROOME COUNTY DEPARTMENT OF PLANNING AND ECONOMIC DEVELOPMENT

312 MAPLE STREET
 VILLAGE OF ENDICOTT, NEW YORK
ERP SITE No. B-00168-7

Conceptual Layout For The Proposed Remedial Action

PROJECT No.
21.0056127.00

FIGURE No.
6

APPENDIX A

RESPONSIVENESS SUMMARY

**312 Maple Street
Environmental Restoration Project
Village of Endicott, Broome County, New York
Site No. B00168**

The Proposed Remedial Action Plan (PRAP) for the 312 Maple Street site was prepared by the New York State Department of Environmental Conservation (the Department) in consultation with the New York State Department of Health (NYSDOH) and was issued to the document repositories on November 9, 2010. The PRAP outlined the remedial measure proposed for the contaminated groundwater, soil, and soil vapor at the 312 Maple Street site.

The release of the PRAP was announced by sending a notice to the public contact list, informing the public of the opportunity to comment on the proposed remedy.

A public meeting was held on November 30, 2010, which included a presentation of the remedial investigation/alternative analysis (RI/AA) for the 312 Maple Street site as well as a discussion of the proposed remedy. The meeting provided an opportunity for citizens to discuss their concerns, ask questions and comment on the proposed remedy. These comments have become part of the Administrative Record for this site. The public comment period for the PRAP ended on December 29, 2010.

There were no public comments received during the public comment period.

APPENDIX B

Administrative Record

**312 Maple Street
Environmental Restoration Project
Village of Endicott, Broome County, New York
Site No. B00168**

1. *Proposed Remedial Action Plan for the 312 Maple Street site*, dated October 2010, prepared by the Department.
2. The Department and the County of Broome entered into a State Assistance Contract, Contract No. C302753, December 15, 2005.
3. “Site Investigation Work Plans, 312 Maple Street, Endicott, New York”, September 2005, prepared by GZA GeoEnvironmental of New York.
4. “Revised Supplemental Remedial Investigation Work Plan, ERP#B00168-7, 312 Maple St., Endicott, NY”, October 2007, prepared by GZA GeoEnvironmental of New York.
5. “Remedial Investigation & Remedial Alternative Report, 312 Maple Street Site, Endicott, New York, NYSDEC Site # B-00168-7”, October 2009, prepared by GZA GeoEnvironmental of New York.
6. “Supplemental Off-Site Interim Remedial Measure Work Plan, ERP#B00168-7, 312 Maple St., Endicott, NY”, September 2010, prepared by GZA GeoEnvironmental of New York.